

APPLICATION INSTRUCTIONS

MY DECK PROJECT









FLOOD® Solid Color

Flood 100% Acrylic Solid Color stain adds a rich opaque color that still showcases the texture of the wood, but completely hides the grain and color of the wood. It has excellent adhesion and provides a mildew resistant and water repellant finish that protects wood from UV rays and mildew stains. See the product label for more information and details regarding application.

- Cover everything you do not wish to coat, including plants.
- Make sure the wood surface has been properly prepared and is completely dry.
- 3. For color uniformity, intermix all containers being used, and do not thin the product.
- 4. Stir the product before and periodically during application.
- 5. Apply an even coat with a brush, roller or airless sprayer, avoiding heavy application.
- If spraying on the product, always backbrush or backroll to improve penetration and uniformity of coverage.
- 7. A second coat is recommended. Wait a minimum of 2 hours and a maximum of 4 hours before the application of second coat.
- 8. Some colors, or drastic color changes, may require a third coat to achieve a uniform Finish.
- 9. Allow the finish to dry 24 to 48 hours.

APPLICATION OPTIONS

- High-quality, bristle stain brush
- Lambswool or mohair roller with 3/8"-3/4" nap
- Pump sprayer
- Airless sprayer (.011 .015 fluid tip, 700 – 800 psi)

WEATHER REQUIREMENTS

- Apply Flood Semi-Transparent Acrylic stain in temperatures between 35° and 120° F.
- If the surface is too hot, lightly mist with water from a garden hose to cool the surface before application
- Do not apply if wet weather is expected within 12 hours.

APPLICATION TIPS

- To avoid lap marks, always work the entire length of a board while maintaining a wet edge. Never stop application in the middle of the board.
- Vertical surfaces should be coated from top to bottom.

CLEANUP

• Clean tools with soapy water.

IMPORTANT NOTES

- · Wear safety glasses.
- Do not apply in direct sunlight or on hot surfaces.
- Flood Semi-Transparent stain is for exterior use only; do not use it indoors.