



APPLICATION INSTRUCTIONS

MY DECK PROJECT



FLOOD® Semi-Transparent Acrylic/Oil

Flood Semi-Transparent Acrylic/Oil stain adds rich, beautiful color that allows the wood grain to show through. Its water repellent finish provides the penetration of an oil and the durability of an acrylic to protect the wood from weathering. See the product label for more information and details regarding application.

1. Cover everything you do not wish to coat, including plants.
2. Make sure the wood surface has been properly prepared and is completely dry.
3. For color uniformity, intermix all containers being used, and do not thin the product.
4. Stir the product before and periodically during application.
5. Apply an even coat with a brush, roller or airless sprayer, avoiding heavy application.
6. If spraying on the product, always backbrush or backroll to improve penetration and uniformity of coverage.
7. A second coat may be applied. Wait a minimum of 4 hours and a maximum of 24 hours before the application of second coat.
8. Allow the finish to dry 24 to 48 hours.

APPLICATION OPTIONS

- High-quality natural bristle stain brush
- Lambswool or mohair roller with 3/8"–3/4" nap
- Pump sprayer
- Airless sprayer (.011 – .015 fluid tip, 700 – 800 psi)

WEATHER REQUIREMENTS

- Apply Flood Semi-Transparent Acrylic stain in temperatures between 35° and 90° F.
- Do not apply if wet weather is expected within 24 hours.

APPLICATION TIPS

- To avoid lap marks, always work the entire length of a board while maintaining a wet edge. Never stop application in the middle of the board.
- Vertical surfaces should be coated from top to bottom.

CLEANUP

- Clean tools with soapy water.

IMPORTANT NOTES

- Wear safety glasses.
- Do not apply in direct sunlight or on hot surfaces.
- Flood Semi-Transparent stain is for exterior use only; do not use it indoors.